

ABB Componenten Zekeringhouder voor 22 x 58mm zekeringen 1 polig , max 100A + indicato

€ 45,00

Beschermingsgraad (IP)	IP20
Aantal polen	1
Montagewijze	DIN-rail
Inbouwdiepte	73,26 mm
Afsluitbaar	Ja
Breedte in module-eenheden	2
Meeschakelende nul	Ja
Met verklikker	Ja
Voor zekeringsgrootte	22 x 58 mm
Model	System pro M compact



ABB

E91/125k

22 x 58

100A

690V~

DO NOT OPEN WHILE UNDER LOAD

DO NOT OPEN WHILE UNDER LOAD

DO NOT OPEN WHILE UNDER LOAD

DO NOT OPEN WHILE UNDER LOAD

DO NOT OPEN WHILE UNDER LOAD

DO NOT OPEN WHILE UNDER LOAD

DO NOT OPEN WHILE UNDER LOAD

DO NOT OPEN WHILE UNDER LOAD

DO NOT OPEN WHILE UNDER LOAD

DO NOT OPEN WHILE UNDER LOAD

DO NOT OPEN WHILE UNDER LOAD

DO NOT OPEN WHILE UNDER LOAD

DO NOT OPEN WHILE UNDER LOAD

DO NOT OPEN WHILE UNDER LOAD

DO NOT OPEN WHILE UNDER LOAD

DO NOT OPEN WHILE UNDER LOAD

DO NOT OPEN WHILE UNDER LOAD

DO NOT OPEN WHILE UNDER LOAD

DO NOT OPEN WHILE UNDER LOAD

DO NOT OPEN WHILE UNDER LOAD

DO NOT OPEN WHILE UNDER LOAD

DO NOT OPEN WHILE UNDER LOAD

DO NOT OPEN WHILE UNDER LOAD

DO NOT OPEN WHILE UNDER LOAD

DO NOT OPEN WHILE UNDER LOAD

DO NOT OPEN WHILE UNDER LOAD

DO NOT OPEN WHILE UNDER LOAD

DO NOT OPEN WHILE UNDER LOAD

DO NOT OPEN WHILE UNDER LOAD

DO NOT OPEN WHILE UNDER LOAD

DO NOT OPEN WHILE UNDER LOAD

DO NOT OPEN WHILE UNDER LOAD

DO NOT OPEN WHILE UNDER LOAD

DO NOT OPEN WHILE UNDER LOAD

DO NOT OPEN WHILE UNDER LOAD

DO NOT OPEN WHILE UNDER LOAD

DO NOT OPEN WHILE UNDER LOAD

DO NOT OPEN WHILE UNDER LOAD

DO NOT OPEN WHILE UNDER LOAD