Finder FIN INTERF.REL MasterPlus 1W 6A 24VUC € 21,63

Nom. stroom	6 A
Beschermingsgraad (IP)	IP20
Breedte	6,2 mm
Hoogte	90,7 mm
Diepte	94,3 mm
Uitvoering elektrische aansluiting	Schroefaansluiting
Aantal contacten als verbreekcontact	0
Aantal contacten als maakcontact	0
Aantal contacten als wisselcontact	1
Bedrijfsspanning bij AC 60 Hz	19.200 - 26.400
Bedrijfsspanning bij AC 50 Hz	19.200 - 26.400
Bedrijfsspanning bij DC	19.200 - 26.400
Type stuurspanning	AC/DC
Nom. stuurspanning Us bij AC 50HZ	24.000 - 24.000 V
Nom. stuurspanning Us bij AC 60HZ	24.000 - 24.000 V
Nom. stuurspanning Us bij DC	24.000 - 24.000 V
Met LED indicatie	Ja
Max. inschakelstroom	10
Materiaal contact	Zilvertinoxide (AgSnO2)
Met afneembare klemmen	Nee
Spanningstype van de bedrijfsspanning	AC/DC
Aandrijving, polarisatie	Ongepolariseerd
Schakelverhouding van de aandrijving	Monostabiel
Type schakelcontact	1-voudig contact
Compleet apparaat met sokkel	Ja
Aandraaimoment	0.500 - 0.500
Model	39
Land van herkomst	Italië (IT)


finder
34.51.7.024.0010
RINA
P05F
24V 6A 250V
Made in Spain
finder
MasterPLUS
A1
14
NO
U_N AC/DC 24-240V
INTERFACE 39.31.0.240.x060
RELAY 34.51.7.024.x010
SOCKET 93.63.0.240
Made in Italy
Finder SpA
I-10040 Almese
11(13+)
COM
COIL
A2
U_N AC/DC 24-240V
INTERFACE 39.30.0.240.xxxx
SSR 34.81.7.024.xxxx
US LISTED
IND.CONT.EQ. 17RZ
39 SERIES ONLY WITH
34 SERIES RELAY
12
NC
6A 250V
RINA
4A 300V 70°C
6A 300V 40°C