

Fluke Intrinsiek veilige drukkalinibrator, 100G

€ 5.688,00

Aantal kanalen	1
Meetwaardegeheugen	Nee
Indicatie/aanduiding	Digitaal
Interface	Nee
Analoge balkaanduiding	Nee
Kleinste resolutie gelijkstroom	1 μ A
Max. stroommeetbereik DC	0,024 A
Meervoudige indicatie	Ja
Thermo-element RTD	Nee
Thermo-element type B	Nee
Thermo-element type E	Nee
Thermo-element type J	Nee
Thermo-element type K	Nee
Thermo-element type N	Nee
Thermo-element type R	Nee
Thermo-element type S	Nee
Thermo-element type T	Nee
Model	Proceskalibrator
Drukmeting	Ja
Spanning geven 0 V ... 10V	Nee
Spanning geven 0 mV ... 100mV	Nee
Stroom geven 0 mA ... 24 mA	Ja
Thermo-element type L	Nee
Thermo-element type U	Nee
Spanning geven 0 V ... +/- 300 mV	Nee
Spanning geven 0 V ... 3 V	Nee
Spanning geven 0 V ... 15 V	Nee
Laagste resolutie stroom geven	0,001 mA
Stroomdaling (transmitter simulator) 0 mA ... 24 mA	Ja
Laagste resolutie stroomdaling	0,001 mA
Weerstand geven	Nee
Thermo-element RTD Pt100	Nee

Thermo-element RTD Pt1000	Nee
Thermo-element RTD Ni100	Nee
Thermo-element RTD Ni1000	Nee
Frequentie en impulsgroepen geven	Nee
Helling- en trapfunctie	Ja
Gelijktijdig meten en geven	Ja
Kalibratiefunctie	Nee
Druk geven (externe drukpomp)	Nee
Land van herkomst	China (CN)

FLUKE 718Ex 100G PRESSURE CALIBRATOR

psi
7.18
9.587 mA



II 1 G EEx ia IIC T4
KEMA 02 ATEX XXXX



REFER TO CONTROL DRAWING:
ANSCHLUSSSCHEMA BEACHTEN:
SUIVRE LE SCHEMA DE CONNEXION:
FLUKE 718Ex CCD



C US
LR110460
AEx ia IIC T4
I.S. Class 1
Div 1 Group A-D



UNITS

DAMP

ZERO

MIN
MAX

CLR

BAROMETRIC ADJ.

SWITCH
TEST

HOLD

RANGE

100psi 689kPa

mA



200psi 1379kPa
MAX

30V
24mA
MAX

COM



FLUKE 700PEX
ONLY

