

## Fluke Intrinsiek veilige drukkalinibrator (20 bar)

€ 5.688,00

|                                                     |                  |
|-----------------------------------------------------|------------------|
| Aantal kanalen                                      | 1                |
| Meetwaardegeheugen                                  | Nee              |
| Indicatie/aanduiding                                | Digitaal         |
| Interface                                           | Nee              |
| Analoge balkaanduiding                              | Nee              |
| Kleinste resolutie gelijkstroom                     | 1 $\mu$ A        |
| Max. stroommeetbereik DC                            | 0,024 A          |
| Meervoudige indicatie                               | Ja               |
| Thermo-element RTD                                  | Nee              |
| Thermo-element type B                               | Nee              |
| Thermo-element type E                               | Nee              |
| Thermo-element type J                               | Nee              |
| Thermo-element type K                               | Nee              |
| Thermo-element type N                               | Nee              |
| Thermo-element type R                               | Nee              |
| Thermo-element type S                               | Nee              |
| Thermo-element type T                               | Nee              |
| Model                                               | Proceskalibrator |
| Drukmeting                                          | Ja               |
| Spanning geven 0 V ... 10V                          | Nee              |
| Spanning geven 0 mV ... 100mV                       | Nee              |
| Stroom geven 0 mA ... 24 mA                         | Ja               |
| Thermo-element type L                               | Nee              |
| Thermo-element type U                               | Nee              |
| Spanning geven 0 V ... +/- 300 mV                   | Nee              |
| Spanning geven 0 V ... 3 V                          | Nee              |
| Spanning geven 0 V ... 15 V                         | Nee              |
| Laagste resolutie stroom geven                      | 0,001 mA         |
| Stroomdaling (transmitter simulator) 0 mA ... 24 mA | Ja               |
| Laagste resolutie stroomdaling                      | 0,001 mA         |
| Weerstand geven                                     | Nee              |
| Thermo-element RTD Pt100                            | Nee              |

|                                          |            |
|------------------------------------------|------------|
| <b>Thermo-element RTD Pt1000</b>         | Nee        |
| <b>Thermo-element RTD Ni100</b>          | Nee        |
| <b>Thermo-element RTD Ni1000</b>         | Nee        |
| <b>Frequentie en impulsgroepen geven</b> | Nee        |
| <b>Helling- en trapfunctie</b>           | Ja         |
| <b>Gelijktijdig meten en geven</b>       | Ja         |
| <b>Kalibratiefunctie</b>                 | Nee        |
| <b>Druk geven (externe drukpomp)</b>     | Nee        |
| <b>Land van herkomst</b>                 | China (CN) |





FLUKE 718Ex 100G PRESSURE CALIBRATOR

psi  
7.18  
9.587 mA



II 1 G EEx ia IIC T4  
KEMA 02 ATEX XXXX



REFER TO CONTROL DRAWING:  
ANSCHLUSSSCHEMA BEACHTEN:  
SUIVRE LE SCHEMA DE CONNEXION:  
FLUKE 718Ex CCD



C US  
LR110460  
AEx ia IIC T4  
I.S. Class 1  
Div 1 Group A-D



UNITS

DAMP

ZERO

MIN  
MAX

CLR

BAROMETRIC ADJ.

SWITCH  
TEST

HOLD

RANGE

100psi 689kPa

mA



30V  
24mA  
MAX

COM

200psi 1379kPa  
MAX



FLUKE 700PEX  
ONLY